

KENWOOD

Listen to the Future

NEXEDGE™

NXR-700/800

NEXEDGE™ VHF/UHF Digital & FM Base Units

NXDN™

FleetSync®
by KENWOOD

● GENERAL FEATURES

- 136-154, 146-174 MHz
- 400-430, 450-480, 480-512 MHz
- 5 W Exciter Output
- 40 / 110 / 250 Watt VHF Systems
- 40 / 100 / 250 Watt UHF Systems
- Repeater Operation
- Duplex/Simplex Base Operation
- 30 CH Scanning Base (Conventional)
- Two-Digit LED Display
- LED Status Indicators
- 6 Programmable Function Keys
- 0.3 W Front Panel Speaker
- 3 W External Speaker Audio
- Volume Control
- Microphone Jack
- Program/Modem Interface
- Remote Termination Interface
- Programmable AUX I/O's
- DTMF Front Panel PF Key Control
- DTMF AUX Output Control
- DTMF AUX Input Monitoring
- KPG-109D Windows® FPU
- Flash Firmware Upgrading

● DIGITAL – COMMON

- NXDN™ Digital Air Interface
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- UID & GID Validation
- NXR Over-the-Air Alias
- KXX-3 OCXO Option (6.25 kHz operation)

● DIGITAL – CONVENTIONAL MODE

- 16 RAN Repeater Controller Built-in
- 1,000 GIDs Per Site
- 1,000 UIDs Per Site
- Mixed FM/Digital Operation
- NXDN™ Scrambler Included

● DIGITAL TRUNKING OPTION

- 3,000 GIDs Per Site
- 3,000 UIDs Per Site
- 30 Channels Per Site
- Transmission Trunked Mode
- Message Trunked Mode
- Call Queuing with Priority
- Call Queue Pre-emption
- Late Entry (UID & GID)
- NXDN™ Scrambled Audio Support
- Cross-Busy
- Fail Soft Mode
- NXDN™ Traffic Channel Sharing
- 2MB Call/Activity Memory
- Compact Flash Memory Expansion

● MULTI-SITE IP NETWORK OPTION

- 16 Site Trunked IP Network
- 60,000 GIDs Per Network
- 60,000 UIDs per Network
- NEXEDGE™ Trunked Features
- Ethernet Network Interface
- IP LAN/WAN Connectivity
- ESN Validation
- Auto-Roaming / Registration

● KPG-110SM SYSTEM MANAGER

- Trunked Sites & IP Network Systems Only
- Windows® 2000/XP/Vista® Compatible
- USB Secure Key Access
- Direct, Dial-Up & IP Connectivity
- Subscriber Privileging
- 127 UID Class Of Service Entries
- 127 GID Class of Service Entries
- 5000 Fleets (UID/GID User Lists)
- Group Call Inter-Site Limits
- Remote Site Programming
- Real-Time Activity Monitoring
- NXR/Network Interface Diagnostics
- Call Logging / Event Download
- Remote System Firmware Updates

● FM MODES – GENERAL

- 25 & 12.5 kHz Channels
- Encryption/ANI Board Control

● FM CONVENTIONAL MODE

- 16 QT/DQT Repeater Control Built-in
- Hang Timer / Time Out Timer / CW ID
- External FM Controller Interface

● FM LTR® TRUNKED MODE

- External LTR® Controller Interface



KenwoodLandMobileRadio
25 Years

Options

- **KXK-3**
OCXO Unit
(Required for
6.25 kHz operation)



- **KMC-9C**
Desktop Microphone



- **KMC-35**
Microphone



- **KES-5**
External Speaker



Main Specifications

All accessories and options may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

GENERAL		NXR-700	NXR-800
Frequency Range	K K2 K3	146-174 MHz 136-154 MHz	450-480 MHz 480-512 MHz (RX) / 477-512 MHz (TX) 400-430 MHz
Channel Spacing	Analog Digital	12.5 / 15 / 25 / 30 kHz 6.25 / 12.5 kHz	12.5 / 25 kHz 6.25 / 12.5 kHz
PLL Channel Step		2.5 / 3.125 / 5 / 6.25 kHz	3.125 / 5 / 6.25 kHz
Frequency Stability	With KXK-3 (for 6.25 kHz)		± 1.5 ppm ± 0.5 ppm
Operating Voltage			13.8 V DC ± 15%
Operating Temperature Range			-22° F to + 140° F (-30° C to +60° C)
Antenna Impedance			50 Ω
Dimensions (W x H x D) Projections not included		19.02 x 1.73 x 13.03 in (483 x 44 x 331 mm)	
Weight (net)		11 lb (5 kg)	
FCC ID	K K2 K3	K44371300 K44371301	K44371400 K44371401 (Pending)
IC Certification	K K2 K3	282F-371300 282F-371301	282F-371400 (Pending)
RECEIVER			
Sensitivity	Digital @ 6.25kHz (3% BER) Digital @ 12.5kHz (3% BER) Analog (12 dB SINAD)		0.27 μV 0.33 μV 0.30 μV
Selectivity	Analog @ 25/30 kHz Analog @ 12.5 kHz	93 dB (± 30 kHz) 85 dB (± 12.5 kHz)	87 dB (± 25 kHz) 81 dB (± 12.5 kHz)
FM Hum & Noise	Analog @ 25/30 kHz Analog @ 12.5 kHz		60 dB 55 dB
Intermodulation Distortion			85 dB (± 50 / 100 kHz)
Spurious Response			100 dB
Audio Distortion (Ext. SP)			Less than 2% (at 0.3W)
Audio Output (Ext. SP)			3 W (at 4Ω, less than 5% distortion)
TRANSMITTER			
RF Power Output			5 W to 0.5 W
Spurious & Harmonics			73 dB
FM Hum & Noise	Analog @ 25/30 kHz Analog @ 12.5 kHz		55 dB 50 dB
Audio Distortion			Less than 1% at 1000 Hz
Modulation			16K0F3E, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D

Analog measurements made per TIA/EIA 603 and specifications shown are typical.
Kenwood reserves the right to change specifications without prior notice or obligation.

FleetSync® is a registered trademark of Kenwood Corporation.
LTR® is a registered trademark of Transcript International.
AMBE+2™ is a trademark of Digital Voice Systems Inc.

Windows® and Windows 2000/XP/Vista® are registered trademarks of Microsoft Corporation.
NXDN™ is a trademark of Kenwood Corporation and Icom Inc.
NEXEDGE™ is a trademark of Kenwood Corporation.

Listen to the Future

Kenwood has always connected with people through sound. Now we want to expand the world of sound in ways that only Kenwood can, listening to our customers and to the pulse of the coming age as we head toward a future of shared discovery, inspiration and enjoyment.

Kenwood U.S.A. Corporation
Communications Sector Headquarters
3970 Johns Creek Court, Suite 100, Suwanee, GA 30024

Kenwood Electronics Canada Inc.
Canadian Headquarters and Distribution
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8

Order Administration/Distribution
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

